

# Femtowatt Photoreceiver with InGaAs-PIN Photodiode




The Photoreceiver will be delivered without post holder and post.

Features	<ul style="list-style-type: none"> <li>• <b>Ultra-Low-Noise, Minimum NEP 7.5 fW/√Hz</b></li> <li>• <b>Amplifier Transimpedance Gain 1 x 10<sup>11</sup> V/A</b></li> <li>• <b>InGaAs-PIN Detector, 0.5 mm Active Diameter</b></li> </ul>	
Applications	<ul style="list-style-type: none"> <li>• <b>Fluorescence Measurements</b></li> <li>• <b>NIR Spectroscopy</b></li> <li>• <b>Electrophoresis</b></li> <li>• <b>Replacement for (liquid nitrogen) cooled Ge-Photodiodes and Avalanche Photodiodes (APDs)</b></li> </ul>	
Specifications	<p>Test Conditions</p> <p>Gain</p> <p>Frequency Response</p> <p>Detector</p> <p>Input</p> <p>Noise</p> <p>Output</p>	<p><math>V_s = \pm 15 \text{ V}, T_a = 25^\circ\text{C}</math></p> <p>Transimpedance Max. Conversion Gain</p> <p>Lower Cut-Off Frequency Upper Cut-Off Frequency Rise/Fall-Time</p> <p>Detector Material Active Area Spectral Response</p> <p>Optical Saturation Power</p> <p>Min. NEP</p> <p>Output Voltage Output Impedance Offset Voltage Max. Output Current</p>

## Femtowatt Photoreceiver with InGaAs-PIN Photodiode


Power Supply	Supply Voltage Supply Current	$\pm 15\text{ V}$ ( $\pm 14.5\text{ V}$ to $\pm 16\text{ V}$ ) $\pm 15\text{ mA}$ typ. (Depends on Operating Conditions, Recommended Power Supply Capability Minimum $\pm 50\text{ mA}$ )
Case	Weight Material	0.19 kg (0.42 lbs) AlMg4.5Mn, nickel-plated
Temperature Range	Storage Temperature Operating Temperature	$-40\text{ }^\circ\text{C}$ to $+100\text{ }^\circ\text{C}$ $0\text{ }^\circ\text{C}$ to $+60\text{ }^\circ\text{C}$
Absolute Maximum Ratings	Optical Input Power Power Supply Voltage	10 mW $\pm 22\text{ V}$



Connectors	Input	Optical, Free Space, 25 mm $\varnothing$ Round Flange Compatible with Microbench Systems
	Output	BNC
	Power Supply	LEMO Series 1S, 3-pin fixed Socket Pin 1: + 15V Pin 2: - 15V Pin 3: GND

# Femtowatt Photoreceiver with InGaAs-PIN Photodiode

Dimensions



DZ-FWPR\_1.cdr

FEMTO Messtechnik GmbH  
 Paul-Lincke-Ufer 34  
 D-10999 Berlin · Germany  
 Tel.: +49 (0)30 – 4 46 93 86  
 Fax: +49 (0)30 – 4 46 93 88  
 e-mail: info@femto.de  
 http://www.femto.de

Specifications are subject to change without notice. Information furnished herein is believed to be accurate and reliable. However, no responsibility is assumed by FEMTO Messtechnik GmbH for its use, nor for any infringement of patents or other rights granted by implication or otherwise under any patent rights of FEMTO Messtechnik GmbH. Product names mentioned may also be trademarks used here for identification purposes only.  
 © 2005 by FEMTO Messtechnik GmbH  
 Printed in Germany